

# An Applied Driving Evaluation of Electrodermal Potential as a Measurement of Attentional State

Bruce Mehler, Ben D. Sawyer, Tom McWilliams, Bryan Reimer

*Massachusetts Institute of Technology, AgeLab, Cambridge, MA, United States*

Traditional electroencephalography (EEG) systems are the gold standard for measuring levels of alertness, have shown mixed but arguably promising results in measuring cognitive workload,<sup>1</sup> and can be used even in applied roadway tasks to detect neural correlates of complex decision-making.<sup>2</sup> However, high-quality, multichannel EEG arrays tend to be expensive and time-consuming to set up. Wrist-wearable electrodermal potential (EDP) devices promise classification of EEG states without such limitations. The lone description of such a device in the present literature describes a generalized measure of attentional state constructed from EDP that achieves accuracy of 84.2% in distinguishing, in a laboratory setting, between relaxed participants with eyes closed and patients actively engaging in visual search.<sup>3</sup> Such a measure, provided it remained reasonably reliable under actual field conditions, would have broad neuroergonomic potential. At the same time, such a system would have to overcome and address a number of technical challenges to practically provide the functionality suggested by the developers. Thus, a careful, realistic, and independent evaluation of this technology under actual driving conditions appeared warranted. As such, the present work sought to evaluate a Freer Logic BodyWave EDP wearable, and, in particular, the attentional index provided by this device, to determine if it could distinguish between levels of demand imposed on a driver. A gender-balanced and age-diverse sample of experienced drivers drove on-road while connected to the EDP wearable as well as a heart monitor. Participants experienced epochs of driving alone, and epochs of driving and being parked while completing a working-memory “n-back” task,<sup>4</sup> in which they were presented with a stream of single-digit numbers and were instructed to either verbalize the number (0-back), the immediately preceding number (1-back), or the number two-places back in the sequence (2-back). It was hypothesized that both heart rate and EDP would be able to distinguish between these levels of load. Heart-rate data indeed showed significant differences between baseline driving and each level, in a pattern suggesting a successful manipulation: the n-back task elevated demand in an orderly fashion, and demand was much higher in the “driving plus n-back” conditions than in the “parked plus n-back” conditions. The EDP attention metrics showed trends that appear to match these patterns, but none reached the level of significance ( $\alpha=0.05$ ). A closer look at the alpha, beta, delta, and theta indices, which underlie the BodyWave EDP wearable-reported attention metric,<sup>3</sup> show some promise, and help explain this orderly but nonsignificant pattern. Nonetheless, it appears that EDP wearables need more development before they are robust to noisy, applied contexts like on-road driving.

## REFERENCES

1. Parasuraman R, Wilson GF. Putting the brain to work: neuroergonomics past, present, and future. *Human Factors* 2008;**50**(3):468–74.
2. Sawyer BD, Karwowski W, Xanthopoulos P, Hancock PA. Detection of error-related negativity in complex visual stimuli: a new neuroergonomic arrow in the practitioner’s quiver. *Ergonomics* 2016:1–7.
3. Kim I, Kim M, Hwang T, Lee CW. Outside the head thinking: a novel approach for detecting human brain cognition. In: *International conference on human-computer interaction*. Springer International Publishing; 2016. p. 203–8.
4. Mehler B, Reimer B, Coughlin JF. Sensitivity of physiological measures for detecting systematic variations in cognitive demand from a working memory task: an on-road study across three age groups. *Human Factors* 2012;**54**(3):396–412.